Codice: 1D0000

Lindos



water-based wall paint for interior and exterior

LINDOS is a water-based paint formulated with stearine coated extenders. Provides perspiring characteristics and is suitable for any internal area, performing a delicate and smooth finish. Applied outdoor it protects the wall surface from heavy rain thanks to its waterproofing characteristics. When applied outdoor It does wear gruadually, thus avoiding leafing or cracking problems. It can be considered as well a washable paint for interior.

Techical Characteristics		Application Da	
Paint Type	Water-based one-component	Application	Brush
	paint	Brush-Roller	20-40
Binder type A	Vinyl versatate	Spray	20-40
Specific gravity kg/lt (±0,05)	1.650	Dust dry	30-40
Solids content (weight) ±2	74%	Recoat time	min. 6
Solids content (volume) ±2	57%	Application temperature	Betwe
Shelf life +23°C (±2)	30 months in unopened cans	Relevant humidity	Less t
Note	Store in a dry and cool place.	Dry film thickness advised	40 dry
	Do not store at low	Theoret. coverage m2/Lt	10
	temperatures.		
Viscosity Ford (Ø4 a 20°C)	20.000±2000 cps		

Application Data		
Application	Brush-Roller-Spray	
Brush-Roller	20-40% with water	
Spray	20-40% with water	
Dust dry	30-40 minutes (20c)	
Recoat time	min. 6-12 hours	
Application temperature	Between +10 C and +40 C	
Relevant humidity	Less than 80%	
Dry film thickness advised	40 dry microns	
Theoret. coverage m2/Lt	10	

SURFACE PREPARATION AND APPLICATION

Bare walls.

The surface should be clean, dry and free from any loosing particles. In case of particular absorbing walls it is recommended that a sealing coat of ISOLFIX or FIXACRIL is applied first, allowing 3-4 hours to dry. Apply 2 coats of LINDOS (slightly more diluted the first coat) allowing the required waiting time between coats.

Painted walls.

In good conditions:

If the old paint is still in good conditions just apply 1-2 coats of LINDOS allowing the required waiting time between coats.

In poor conditions:

Remove any loose or powdery pre-existing paint by wirebrushing. If necessary apply a sealing coat of ISOLFIX on a dry and clean surface. Apply 2 coats of LINDOS allowing the required waiting time between coats.







Codice: 1D0000 Lindos



SAFETY PRECAUTIONS

Before starting paint application please carefully read all the safety precautions indicated on the label of each can or in the product safety data sheet available on request. For further information please do not hesitate to contact our technical staff.

NOTES

The above information is given to the best of our current knowledge, however, because the conditions of use of our products are beyond our control, no warranty is given or to be implied in respect of such information. Our technical staff can be contacted to study customer's specific requirements involving our products in order to enable their most effective use. Dilution rates and drying times must be considered only indicative, mainly related to a temperature of 20 °C (68°F) and may vary according to prevailing temperature, in presence of particular weather conditions or depending on application procedures.





